

OPTIDI

USER GUIDE

valid from June 2018

Architected Sound

Chałubińskiego 53
30-698 Kraków, Poland
info@architected-sound.com
+48 12 259 13 00
www.architected-sound.com

BASIC DATA

product name	OptiDi
product description	acoustic diffuser, made of specially profiled aluminum, ensures sound dispersion in a wide frequency range and absorption of low tones
producer	RS Minus sp. z o.o. Chałubińskiego 53, 30-698 Kraków, Poland TIN: PL 676-243-60-70

PRODUCT CHARACTERISTICS

acoustics	sound absorption coefficient: $\alpha_{w, \max} = 0.20$
fire safety	made out of materials with flammability class A1
dimensional tolerance	+/- 2 mm for single element dimensions
finish	the surface structure depends in each case on the selected type of painting and paint colour

TRANSPORT, STORAGE, ASSEMBLY, CLEANING

transport	protect against excessive sunlight, precipitation and moisture; protect system edges and external components in packages from damage; transport in a horizontal position; loading spaces should be dry and clean, and the surfaces of walls and floors should not have protruding and sharp elements that could cause damage to the product;
storage	store in a horizontal position; the storage room should protect against direct water exposure, excess moisture (over 60%) and drastic temperature changes; do not expose to mechanical damage caused by overturning, warping, hitting with a heavy object, etc.; do not store in passages and at a distance less than 1.0 m from active heating devices;
assembly	according to the manufacturer's instructions; install in rooms protecting against water, excess moisture (over 60%) and drastic temperature changes;
cleaning	clean with a dust cleaner and a dry, soft cloth; cleaning with other means (e.g. dishwashing liquid) or detergents, as well as with damp or wet cloths may cause deformation of elements and damage to their top structure;