UP-SORBER ROLL architected sound

UP-SORBER ROLL

One space, diverse capabilities







mid tone





high tone

UP-SORBER ROLL is an electrically adjustable banner that can change room's acoustic conditions in the blink of an eye.

Customizing the space function has never been so quick and convenient.







UP-SORBER ROLL








absorption

mid tones

high tones

Up-Sorber Roll was created to meet the requirements of adjusting the acoustics in multifunctional spaces. This purpose was achieved by designing the fabric surface rolled up or down to any length required to fit particular environment. Thanks to dedicated control system, setting proper acoustics has never been easier.







Size

width: standard 1.4 m, max 2.5 m length: max 5.0 m

Weight

ca. 26 kg

Material

absorptive fabric

Available in various sizes according to individual project.

colours



Designer

Architected Sound Team

architected sound

Country of production

Poland

Category

absorption

Description

Up-Sorber Roll contains an expandable surface made of textile materials, ensuring the regulation of reverberation time in the range of medium and high tones by increasing the acoustic absorption of the interior and eliminating the first reflections of the sound.

Up-Sorber Roll can be made of one or two layers of textile. The latter increases acoustic absorption in low frequencies and allows obtaining maximum uniformity of acoustic conditions in the whole room.

The system is designed to be installed on walls or ceilings. Specialized mounting procedure required due to individual character of each pro-

Sound absorption coefficient

 $\alpha_{\text{w max}} = 0.65$

Application

Multifunctional rooms, concert halls, theaters, lecture and conference rooms, home listening rooms, rooms in buildings under the supervision of the conservator.

Control

The electric drive is equipped with adjustable limit switches. Wired or radio control, with the ability to group more banners. Possibility of integration with external control systems.


Drive parameters: power supply: 230 V power consumption during operation: max 200 W

Custom-made

Non-standard length and width possible. Possibility of creating a passive surface that can be made of materials ensuring free air flow, such as steel cables or mesh.

Made of materials with flammability class B-s2. d0.

Architected Sound Up-Sorber Roll – sound absorption coefficients



Practical sound absorption coefficient α_p

frequency 1/1-oct.	_
125 Hz	0.15
250 Hz	0.40
500 Hz	0.75
1000 Hz	0.85
2000 Hz	0.65
4000 Hz	0.65

distance of the expanded surface from the wall: 100 mm



Architected Sound

ul. Chalubinskiego 53 30-698 Krakow, Poland info@architected-sound.com +48 12 259 13 00

www.architected-sound.com

